

# The International Code Council's International Property Maintenance Standards

## I. Overview

The nation's model housing or property maintenance code is the [International Property Maintenance Code \(IPMC\)](#). The IPMC is managed by the International Code Council (ICC). Two states – New York and Virginia – and more than 600 local jurisdictions have adopted the IPMC with modifications.

The [International Code Council \(ICC\)](#) published the first edition of the *International Property Maintenance Code* in 1998. ICC's three charter members of the International Code Council – Building Officials and Code Administrators International, Inc. (BOCA), International Conference of Building Officials (ICBO), and Southern Building Code Congress International (SBCCI) – developed the IPMC as a comprehensive set of regulations for existing buildings that was consistent with the existing model property maintenance codes at the time. A new edition is promulgated every three years.

The *International Property Maintenance Code* is founded on principles that the IPMC must:

1. Adequately protect public health, safety, and welfare;
2. Not unnecessarily increase construction costs;
3. Not restrict the use of new materials, productions, or methods of construction; and
4. Not give preferential treatment to particular types or classes of materials, products, or methods of construction.

## Adoption

The *International Property Maintenance Code* is available for adoption and use by jurisdictions internationally. Its use within a governmental jurisdiction is intended to be accomplished through adoption by reference. At the time of adoption, jurisdictions should insert the appropriate information in provisions requiring specific local information, such as the name of the adopting jurisdiction. These locations are shown in bracketed words in small capital letters in the code and in the sample ordinance.

Visit [https://www.iccsafe.org/wp-content/uploads/Code\\_Adoption\\_Maps.pdf](https://www.iccsafe.org/wp-content/uploads/Code_Adoption_Maps.pdf) to learn whether the *International Property Maintenance Code* or any of the other ICC Codes have been adopted in your community.

## **Maintenance**

The *International Property Maintenance Code* is kept up to date through the review of proposed changes submitted by code enforcing officials, industry representatives, design professionals and other interested parties. Proposed changes are carefully considered through an open code development process in which all interested and affected parties may participate. The contents of the code are subject to change both through the Code Development Cycles and the governmental body that enacts the code into law. For more information regarding the code development process, contact the Code and Standard Development Department of the International Code Council.

While the development procedure of the *International Property Maintenance Code* assures the highest degree of care, ICC and the founding members of ICC—BOCA, ICBO, SBCCI—their members and those participating in the development of the code do not accept any liability resulting from compliance or noncompliance with the provisions because ICC and its founding members do not have the power or authority to police or enforce compliance with the contents of the code. Only the governmental body that enacts the code into law has such authority.

One advantage of the IPMC is this process of ongoing improvement. Communities that adopt the IPMC often simply update their code to incorporate the latest version of the IPMC. In contrast, most local codes do not have a regular process for improvement and refinement. These communities often lack the resources to undergo a careful review and political factors lock in the existing code unless serious problems arise.

## **Relationship to Other ICC Codes**

The *International Property Maintenance Code* complements and is fully compatible with all the *International Codes* (“I-Codes”) published by the International Code Council (ICC), including the:

1. International Building Code;
2. ICC Electrical Code;
3. International Energy Conservation Code;
4. International Existing Building Code;
5. International Fire Code;
6. International Fuel Gas Code;
7. International Mechanical Code;
8. ICC Performance Code;
9. International Plumbing Code;
10. International Private Sewage Disposal Code;
11. International Residential Code;
12. International Urban-Wildland Interface Code; and
13. International Zoning Code.

All but three other states have adopted one or more of these model codes – most likely the International Building Code.

## II. IPMC's Provisions Related to Healthy Homes

**EXTERMINATION.** The control and elimination of insects, rats or other pests by eliminating their harborage places; by removing or making inaccessible materials that serve as their food; by poison spraying, fumigating, trapping or by any other approved pest elimination methods.

**HABITABLE SPACE.** Space in a structure for living, sleeping, eating or cooking. Bathrooms, toilet rooms, closets, halls, storage or utility spaces, and similar areas are not considered habitable spaces.

**INFESTATION.** The presence, within or contiguous to, a structure or premises of insects, rats, vermin or other pests.

**302.1 Sanitation.** All exterior property and premises shall be maintained in a clean, safe and sanitary condition. The occupant shall keep that part of the exterior property which such occupant occupies or controls in a clean and sanitary condition.

**302.2 Grading and drainage.** All premises shall be graded and maintained to prevent the erosion of soil and to prevent the accumulation of stagnant water thereon, or within any structure located thereon.

**302.5 Rodent harborage.** All structures and exterior property shall be kept free from rodent harborage and infestation. Where rodents are found, they shall be promptly exterminated by approved processes which will not be injurious to human health. After extermination, proper precautions shall be taken to eliminate rodent harborage and prevent reinfestation.

**304.2 Protective treatment.** All exterior surfaces, including but not limited to, doors, door and window frames, cornices, porches, trim, balconies, decks and fences shall be maintained in good condition. Exterior wood surfaces, other than decay-resistant woods, shall be protected from the elements and decay by painting or other protective covering or treatment. Peeling, flaking and chipped paint shall be eliminated and surfaces repainted. All siding and masonry joints as well as those between the building envelope and the perimeter of windows, doors, and skylights shall be maintained weather resistant and water tight. All metal surfaces subject to rust or corrosion shall be coated to inhibit such rust and corrosion and all surfaces with rust or corrosion shall be stabilized and coated to inhibit future rust and corrosion. Oxidation stains shall be removed from exterior surfaces. Surfaces designed for stabilization by oxidation are exempt from this requirement.

**304.5 Foundation walls.** All foundation walls shall be maintained plumb and free from open cracks and breaks and shall be kept in such condition so as to prevent the entry of rodents and other pests.

**304.6 Exterior walls.** All exterior walls shall be free from holes, breaks, and loose or rotting materials; and maintained weatherproof and properly surface coated where required to prevent deterioration.

**304.7 Roofs and drainage.** The roof and flashing shall be sound, tight and not have defects that admit rain. Roof drainage shall be adequate to prevent dampness or deterioration in the walls or interior portion of the structure. Roof drains, gutters and downspouts shall be

maintained in good repair and free from obstructions. Roofwater shall not be discharged in a manner that creates a public nuisance.

**304.14 Insect screens.** During the period from [DATE] to [DATE], every door, window and other outside opening required for ventilation of habitable rooms, food preparation areas, food service areas or any areas where products to be included or utilized in food for human consumption are processed, manufactured, packaged or stored, shall be supplied with approved tightly fitting screens of not less than 16 mesh per inch (16 mesh per 25 mm) and every swinging door shall have a self-closing device in good working condition.

**Exception:** Screens shall not be required where other approved means, such as air curtains or insect repellent fans, are employed.

**304.17 Guards for basement windows.** Every basement window that is openable shall be supplied with rodent shields, storm windows or other approved protection against the entry of rodents.

**305.1 General.** The interior of a structure and equipment therein shall be maintained in good repair, structurally sound and in a sanitary condition. Occupants shall keep that part of the structure which they occupy or control in a clean and sanitary condition. Every owner of a structure containing a rooming house, housekeeping units, a hotel, a dormitory, two or more dwelling units or two or more nonresidential occupancies, shall maintain, in a clean and sanitary condition, the shared or public areas of the structure and exterior property.

**305.3 Interior surfaces.** All interior surfaces, including windows and doors, shall be maintained in good, clean and sanitary condition. Peeling, chipping, flaking or abraded paint shall be repaired, removed or covered. Cracked or loose plaster, decayed wood and other defective surface conditions shall be corrected.

**307.1 Accumulation of rubbish or garbage.** All exterior property and premises, and the interior of every structure, shall be free from any accumulation of rubbish or garbage.

**308.1 Infestation.** All structures shall be kept free from insect and rodent infestation. All structures in which insects or rodents are found shall be promptly exterminated by approved processes that will not be injurious to human health. After extermination, proper precautions shall be taken to prevent reinfestation.

**308.2 Owner.** The owner of any structure shall be responsible for extermination within the structure prior to renting or leasing the structure.

**308.3 Single occupant.** The occupant of a one-family dwelling or of a single-tenant nonresidential structure shall be responsible for extermination on the premises.

**308.4 Multiple occupancy.** The owner of a structure containing two or more dwelling units, a multiple occupancy, a rooming house or a nonresidential structure shall be responsible for extermination in the public or shared areas of the structure and exterior property. If infestation is caused by failure of an occupant to prevent such infestation in the area occupied, the occupant shall be responsible for extermination.

**308.5 Occupant.** The occupant of any structure shall be responsible for the continued rodent and pest-free condition of the structure.

**Exception:** Where the infestations are caused by defects in the structure, the owner shall be responsible for extermination.

**403.1 Habitable spaces.** Every habitable space shall have at least one openable window. The total openable area of the window in every room shall be equal to at least 45 percent of the minimum glazed area required in Section 402.1.

**Exception:** Where rooms and spaces without openings to the outdoors are ventilated through an adjoining room, the unobstructed opening to the adjoining room shall be at least 8 percent of the floor area of the interior room or space, but not less than 25 square feet (2.33m<sup>2</sup>). The ventilation openings to the outdoors shall be based on a total floor area being ventilated.

**403.2 Bathrooms and toilet rooms.** Every bathroom and toilet room shall comply with the ventilation requirements for habitable spaces as required by Section 403.1, except that a window shall not be required in such spaces equipped with a mechanical ventilation system. Air exhausted by a mechanical ventilation system from a bathroom or toilet room shall discharge to the outdoors and shall not be recirculated.

**403.4 Process ventilation.** Where injurious, toxic, irritating or noxious fumes, gases, dusts or mists are generated, a local exhaust ventilation system shall be provided to remove the contaminating agent at the source. Air shall be exhausted to the exterior and not be recirculated to any space.

**403.5 Clothes dryer exhaust.** Clothes dryer exhaust systems shall be independent of all other systems and shall be exhausted in accordance with the manufacturer's instructions.

**503.4 Floor surface.** In other than dwelling units, every toilet room floor shall be maintained to be a smooth, hard, nonabsorbent surface to permit such floor to be easily kept in a clean and sanitary condition.

**505.4 Water heating facilities.** Water heating facilities shall be properly installed, maintained and capable of providing an adequate amount of water to be drawn at every required sink, lavatory, bathtub, shower and laundry facility at a temperature of not less than 110° F (43° C). A gas-burning water heater shall not be located in any bathroom, toilet room, bedroom or other occupied room normally kept closed, unless adequate combustion air is provided. An approved combination temperature and pressure-relief valve and relief valve discharge pipe shall be properly installed and maintained on water heaters.

**602.2 Residential occupancies.** Dwellings shall be provided with heating facilities capable of maintaining a room temperature of 68° F (20° C) in all habitable rooms, bathrooms and toilet rooms based on the winter outdoor design temperature for the locality indicated in Appendix D of the *International Plumbing Code*. Cooking appliances shall not be used to provide space heating to meet the requirements of this section.

**Exception:** In areas where the average monthly temperature is above 30° F (-1° C), a minimum temperature of 65° F (18° C) shall be maintained.

**602.3 Heat supply.** Every owner and operator of any building who rents, leases or lets one or more dwelling unit, rooming unit, dormitory or guestroom on terms, either expressed or implied, to furnish heat to the occupants thereof shall supply heat during the period from [DATE] to [DATE] to maintain a temperature of not less than 68° F (20° C) in all habitable rooms, bathrooms, and toilet rooms.

**Exceptions:**

1. When the outdoor temperature is below the winter outdoor design temperature for the locality, maintenance of the minimum room temperature shall not be required provided that the heating system is operating at its full design capacity. The winter outdoor design temperature for the locality shall be as indicated in Appendix D of the *International Plumbing Code*.

2. In areas where the average monthly temperature is above 30° F (-1° C) a minimum temperature of 65° F (18° C) shall be maintained.

**603.2 Removal of combustion products.** All fuel-burning equipment and appliances shall be connected to an approved chimney or vent.

**Exception:** Fuel-burning equipment and appliances which are labeled for unvented operation.

**603.5 Combustion air.** A supply of air for complete combustion of the fuel and for ventilation of the space containing the fuel-burning equipment shall be provided for the fuel-burning equipment.

**603.6 Energy conservation devices.** Devices intended to reduce fuel consumption by attachment to a fuel-burning appliance, to the fuel supply line thereto, or to the vent outlet or vent piping therefrom, shall not be installed unless labeled for such purpose and the installation is specifically approved.

**607.1 General.** Duct systems shall be maintained free of obstructions and shall be capable of performing the required function.