



Formaldehyde in High Performance Homes with Outdoor Air Intakes

Melissa Malkin-Weber

Advanced Energy, Raleigh, North Carolina

Translating Research into Healthy Homes Improvements Series

Presented 3/16/2009



Study Partners

- ▶ HUD Office of Healthy Homes and Lead Hazard Control
- ▶ Advanced Energy
- ▶ National Institutes of Environmental Health Sciences (NIH)
- ▶ UNC School of Medicine Center for Environmental Medicine, Asthma, and Lung Biology
- ▶ Habitat for Humanity



Outline

- ▶ Why formaldehyde?
- ▶ High performance house context
- ▶ Study Hypothesis
- ▶ Intervention specifications
- ▶ Measurement method
- ▶ Results
- ▶ What does that mean?
- ▶ Next steps



Why Measure Formaldehyde in Houses?

- ▶ Human carcinogen (probable)
- ▶ Short term effects
 - > respiratory irritation
 - > eye irritation
- ▶ Suggestive evidence of links to respiratory symptoms
- ▶ Multiple indoor sources



Formaldehyde Sources Indoors

- ▶ Building and Consumer Products
 - > Pressed wood products (urea-formaldehyde resins)
 - > Urea-formaldehyde foam insulation
 - > Fabric finishes
 - > Paper products
 - > Cosmetics
 - > Detergents
 - > More
- ▶ Combustion (heaters or furnaces)
- ▶ Secondary reactions
 - > Terpenes interact with ozone to produce formaldehyde and other byproducts
- ▶ People



Study Hypothesis

- ▶ A high performance home specification can improve the indoor environment related to asthma-relevant outcomes, overcoming homeowner behaviors.
- ▶ High performance (in the real world)
 - > Specifications
 - > Construction processes
 - > Quality assurance testing
 - > Feedback loop (comfort & energy guarantee)
 - > Reality, not just modeled performance
- ▶ Don't rely on homeowner behaviors




Methods - Study Design

- ▶ 36 homes in central North Carolina (mixed humid climate)
- ▶ 20 intervention (“healthy homes intervention package”)
 - > High performance builder process
- ▶ 16 non-intervention homes
 - > Building-code compliant construction
 - > Typical construction





Features of the Intervention



Source: *Environments for Living*

- ▶ Tight construction
- ▶ Interior moisture management
- ▶ Improved insulation
- ▶ “Right-sized” HVAC
- ▶ Pressure balancing
- ▶ Outside air ventilation
- ▶ Closed crawl space



Reality-Ready Research

- ▶ No source control specified (formaldehyde or other volatile organic compounds).
- ▶ Builders used their typical carpets and cabinetry
- ▶ Study participants not asked change behaviors



The Ventilation Package

- ▶ Goal is to provide outside air to dilute pollutants generated indoors
- ▶ Offset the reduced infiltration through the envelope and ducts when house is tightened
- ▶ Used in 2 successful high performance homes programs



Exhaust Ventilation

- ▶ Spot exhaust
- ▶ Performance tested
 - > Kitchen (exhausts >100 cfm)
 - > Baths (exhausts >50 cfm)





Dilution

- ▶ Outdoor air intake with Air Cycler
- ▶ 20 minutes per hour
- ▶ Flow
 - > 10 cubic feet per minute (CFM) in each bedroom plus 10 CFM.
 - > A 3 bedroom house → 40 CFM
 - > Equivalent to ASHRAE 62.2 on intermittent basis





Outdoor Air Intake Configuration

- ▶ Six-inch flex duct
- ▶ Vent at the foundation connected to return air plenum
- ▶ Six-inch manual balancing damper in flex duct near outside intake
- ▶ Damper performance tested
- ▶ Cleanable filter installed at intake





Home Characteristics

	Intervention	Non-intervention	% Difference (I from N)
Duct leakage	34 (3.0%) ¹	122 (10.4%) ¹	72% tighter
Home leakage	862 (0.25) ²	1142 (0.31) ²	25% tighter
Floor area	1143 ft ²	1192 ft ²	4% smaller
Envelope area	3466 ft ²	3619 ft ²	4% smaller

¹ Percentage represents CFM25 duct leakage per square foot floor area.
6% to outdoors is the Energy Star Program standard

² Number in parentheses represents CFM50 home leakage per square foot envelope area



Exhaust

	Intervention	Non-Intervention	% Difference (I from N)
Kitchen exhaust	106 cfm	0	n/a
Bath 1 exhaust	58 cfm	38 cfm	53% higher
Bath 2 exhaust	56 cfm	37 cfm	52% higher



Is the Ventilation Reducing Chemical Pollutants?

- ▶ Seven-day formaldehyde sample
- ▶ 40-day period beginning August 2005 (all humid season)
- ▶ Length of time to offgas varied
 - > Median age of the intervention homes was 10 months (minimum 5 months)
 - > Median age of non-intervention homes was 20 months



Average Formaldehyde Levels

Status	Weight [ppb]	St Dev [ppb]
Intervention	69	22
Non-Intervention	64	25
All	67	25




Available Guidelines

- ▶ 100 ppb action level (Health Canada and the World Health Organization)
- ▶ 40 ppb eight-hour average (Health Canada)
- ▶ 7 ppb eight-hour and chronic Reference Exposure Level (California)



Home by Home





Summary

- ▶ The high performance program didn't harm the homeowners
 - > Tight envelope and tight ductwork did not create higher levels of formaldehyde ...
 - > Compared to homes with unplanned ventilation (duct and envelope leakage).
 - > Ventilation package seems to have compensated for reducing the infiltration & leakage
- ▶ But formaldehyde levels are still above guidance standards
 - > At 10 months after move-in for intervention homes
 - > At 20 months after move-in for non-intervention homes



What Can We Do to Reduce Formaldehyde *(and the rest of the chemicals in the soup)?*

- ▶ Continuous ventilation may be “enough” outdoor air to dilute formaldehyde
- ▶ How do we get “continuous” without moisture overload?
 - ERV
 - Ventilating dehumidifier
 - Other?
- ▶ Considerations:
 - > Tradeoff between moisture and dilution
 - > How much moisture is introduced?
 - > Energy penalty?
 - > Initial and operational costs?



Source Control

- ▶ Formaldehyde in wood products may drop
 - > California regulations
 - > EPA intends to regulate
- ▶ Formaldehyde in other products?
- ▶ Other VOCs in building materials and consumer products...

Melissa Malkin-Weber

Research Director for Applied Building Science

(919) 857-9000

mweber@advancedenergy.org

www.healthierhomes.org



www.advancedenergy.org



References

- ▶ Health Canada. Residential Indoor Air Quality Guideline: Formaldehyde. Ottawa, Ontario, April 2006.
- ▶ Centers for Disease Control and Prevention (CDC). Final report on formaldehyde levels in FEMA-supplied travel trailers, park models, and mobile homes July 2, 2008
- ▶ Davis B, Dastur C. Moisture performance of closed crawl spaces and their impact on home cooling and heating energy in the southeastern United States. U.S. Department of Energy Oak Ridge National Laboratory and ASHRAE Performance of the Exterior Envelopes of Whole Buildings IX International Conference 2004. Clearwater Beach, Florida.
- ▶ Destallats H. Indoor chemistry of ozone with household product constituents. ASHRAE IAQ 2007 Conference. Baltimore, Maryland.
- ▶ Grimsrud DT, Turk BH, Prill RJ, Harrison J, Revzan KL. Effects of house weatherization on indoor air quality. Indoor Air '87: Proceedings of the 4th International Conference on Indoor Air Quality and Climate, Berlin (West). August 1987.
- ▶ Guo L, and Lewis JO. Carbon dioxide concentration and its application on estimating the air change rate in typical Irish houses. International Journal of Ventilation 2007; Vol 6, No 3.
- ▶ Hodgson AT, Beal D. Sources of formaldehyde, other aldehydes and terpenes in a new manufactured house. E.O. Lawrence Berkeley National Laboratory 2002. Contract2002. Contract number DE-AC03-76SF00098. Available at <http://eande.lbl.gov/ied/viaq/>.
- ▶ Kelly TJ, Smith DL, Satola J. Emission rates of formaldehyde from materials and consumer products found in California Homes. Environmental Science and Technology 1999; 33: 81-88.
- ▶ Loh, MM, Levy JI, Spengler JD, Houseman EA, Bennett DH. Ranking cancer risks of organic hazardous air pollutants in the united states. Environmental Health Perspectives 2007; Vol 115, Num 8.

(continued next slide)



References, continued

- ▶ Malkin-Weber M, Coulter J, Hannas B, Dixon T. High performance intervention houses in north carolina – an attempt to control indoor relative humidity at 50% year round. Indoor Air 2008, Copenhagen, Denmark. <http://www.indoorair2008.org/>.
- ▶ Meier, A. Infiltration: just ACH50 divided by 20? Home Energy, 1994
- ▶ Mendell, MJ. Indoor residential chemical emissions as risk factors for respiratory and allergic effects in children: a review. Indoor Air 2007; 17: 259–277
- ▶ Office of Environmental Health Hazard. Assessment Technical Support Document For the Derivation of Noncancer Reference Exposure Levels, [Appendix D.1 Individual Acute, 8-Hour, and Chronic Reference Exposure Level Summaries](#). Oakland: California 2008
- ▶ Offerman F, Brennan S, Roberson J, Springer D Woo T. Window Usage, Ventilation, and Formaldehyde Concentrations in New California Homes: Summer Field Sessions. ASHRAE IAQ 2007 Conference, Baltimore, Maryland.
- ▶ WHO - World Health Organization. Environmental health criteria for formaldehyde. 1989. Geneva, Switzerland: World Health Organization; Volume 89



- ▶ Following are additional slides with supplementary information that will be discussed further in final report and articles



Hypothesis Testing

- ▶ Is the ventilation sufficient to:
 - > Do no harm?
 - > Create BETTER indoor air quality than in houses with leaky shells and ducts?



Field Research in Occupied Houses

► Challenges

- > Scheduling large sample of homes – weekend/evenings
- > Ensuring pickup in acceptable time window
- > Ensuring samples labeled accurately and observational data collected accurately in often-chaotic environment



Snapshot of Ventilation Rates (Air Changes Per Hour) *excluding* impact of air cyclers and ventilation fans

Group	Average ACH at 50 Pa (measured)	Average ACH Natural (calculated)
Intervention	5.7	0.3
Non-Intervention	7.2	0.4



Sampling Method

- ▶ UMEx 100 Passive Samplers (3M)
- ▶ Level of detection of 0.03 ug (2 ppb)





Formaldehyde Sampling

- Deployed in the central hall of the homes
- Transported on ice, stored in refrigerator






7 Steps to high-performance housing

- ▶ Standards
- ▶ Plan Review
- ▶ Contractor/Subcontractor training
- ▶ On-site quality control
- ▶ Performance testing
- ▶ Certification/Guarantee
- ▶ Servicing the Guarantee

TOTAL INTERVENTION COST*		
Upgrade	Study cost per house [2003] Materials & installation	Market cost per house [2007] Materials & installation
<i>SystemVision</i>	\$1,725 per house	\$1,920 - \$2,100 per house
<i>SystemVision</i> fee	\$1,050	\$1,050
Closed crawl space	~\$2.50 per square foot [\$3,00 for 1200 square foot house]	\$1.00 - \$2.50 per square foot [\$1,200 for 1200 square foot house]
Aprilaire	\$170 [Spaceguard filter & frame] \$200-\$800 [installation] *Based on 1200 square foot house at lowest estimate	Same
Total per house	\$6,145	\$4,540



advancedenergy.org



SYSTEMVISION UPGRADE ESTIMATES*			
Standard	Upgrade	Study estimate per home [2003]	Market estimate per home [2007]
1	Proper blocking and building air tightness	\$75	\$100
2	Whole-house mechanical ventilation	\$200	\$100
	Bath and kitchen exhaust upgrades	\$300	\$300
3	Proper insulation installation	\$300	\$150
	Attic insulation increase to R-38		\$100
	Raised heel trusses	\$250	\$250
	Low-E windows	\$150	\$150
4	Outdoor thermostat[s] on heat pump[s]	\$100	
	14 SEER heat pump		\$600
	90% Efficient furnace with 13 SEER air conditioner		\$400
	Proper duct sealing	\$100	\$100
5	Pressure balance and relief	\$150	\$150
6	Electric or gas water heater efficiency upgrade	\$100	\$100
7	Carbon Monoxide detector if applicable		\$20
Total	Electric package total [per home]	\$1,725	\$2,100
	Gas package total [per home]	\$1,725	\$1,920



advancedenergy.org



Number of homes submetered

ENERGY PERFORMANCE MEASUREMENT		
House Type	Number in Group	Number Submetered
Non-Intervention w/ Retrofit	7	7
Non-Intervention	7	7*
Intervention	16	8


* Submetered later in the study



advancedenergy.org



Baseload analysis w/out DHW and Base outliers




advancedenergy.org



► Results – energy use


Energy use breakdown across house type



Space conditioning saving

- > 13.7% total (~5.8% of total energy savings)
- > 3.6% June – August/ 0.8% July – September
- > Intervention homes use more energy in every other category (non-space conditioning)

Energy use breakdown across house type w/out outliers




2006-2007 Space conditioning – intervention houses use 13.7% less energy



advancedenergy.org




Percent of total usage



advancedenergy.org



Average energy use breakdown across all homes




advancedenergy.org



Number of people per house

- ▶ National household size of 2.57 people
- ▶ 2.49 for NC
 - > 2.51 for Wake Co.
 - 2.30 for Raleigh
 - > 2.40 for Durham Co.
 - 2.37 for Durham
- ▶ 4.14 for this study



Level	Count	Prob
2	7	0.19444
3	6	0.16667
4	6	0.16667
5	10	0.27778
6	6	0.16667
7	1	0.02778
Total	36	1.00000




advancedenergy.org





Health and Energy Performance – The Tip of the Iceberg





Phase 2 -- Ventilation

- ▶ Comparison of houses is more “apples to apples”
 - > Measure tight houses with and without outdoor air (no air cyclers)
 - > Measure tight houses with air cyclers
 - > Measure leakier houses without air cyclers
 - > Older houses – longer to offgas



Next Steps

- ▶ Change Intervention Configuration
 - > Mechanical dehumidification (<50% RH)
 - > More affordable closed crawl configuration
- ▶ Measure More Precisely
 - > Pollutants
 - > Air changes per hour
 - > Does filtration change anything?